

4" DoubleDiaphragm Pump

4DD-YD-SK-13 4-Inch Diaphragm Pump



SPECIFICATIONS

| | |
|-----------------|--|
| Volume: | 327gpm / 19,620 GPH |
| Run Time: | 52 Hours Per 13 Gallon Tank |
| Valve Seats: | Stainless Steel |
| Valve Assembly: | Flapper Style with Stainless Hardware |
| Diaphragm: | Red Neoprene Rubber |
| Gear Box: | Worm Gear Oil Lubricated |
| Diaphragm Rods: | Solid Connecting Rods |
| Solid Handling | Solids handling cap. Up to 3.5" diameter |

ENGINE

| | |
|----------------|----------------------------------|
| Model: | Yanmar L100 Diesel |
| Type: | Air Cooled |
| Start: | 12 Volt Electric w/Backup Recoil |
| Fuel: | Diesel fuel |
| Fuel Tank Cap. | 13 Gallons |
| Horsepower | 5.0 @ 2000rpm |

PACKAGE

| | |
|--------|------------------|
| Axle | Forklift Pockets |
| Wheels | N/A |
| Hitch | N/A |
| Weight | 1150 lbs |

OPTIONS

- Larger fuel tank for longer run
- Trailer Mounted
- Sound Enclosure

STANDARD FEATURES

- * Lifting Bail
- *4" Male Cams
- *Coupling Guard
- *Engine Protector
- *Low Oil Shutdown
- *Locking Battery Box

Portable Pumping Systems Inc.
4760 Spring Ave-Clearwater, FL 33762
www.PortablePumpingSystems.com
Donnie@PortablePumpingSystems.com
PH: (727) 518-9191
FAX: (727) 525-1511